










# Alcoa Accessory Catalog











*Europe, edition 2*












**ALCOA**

	Product	Content	Part nr.	Description
<b>CLEANING PRODUCTS</b>				
	ALclean	1 litre bottle	GAXALC001EIS	Wheel cleaner for aluminium wheels. Removes disc brake dust. Eliminates oxidation and keeps the shine. For best results use ALbrush.  Not for Dura-Bright®.
	ALclean	5 litre can	GAXALC005EIS	Wheel cleaner for aluminium wheels. Removes disc brake dust. Eliminates oxidation and keeps the shine. For best results use ALbrush.  Not for Dura-Bright®.
	ALclean	25 litre can	GAXALC025EIS	Wheel cleaner for aluminium wheels. Removes disc brake dust. Eliminates oxidation and keeps the shine. For best results use ALbrush.  Not for Dura-Bright®.
	ALbrush	1 piece	GAXALB001	Soft Alcoa brush to activate the components of ALclean in the most efficient way. Also recommended for Dura-Bright® in combination with pH mild detergents.
	ALpolish	200 g tube	GAXALP200EIS	Polishing compound to restore the shine of your Alcoa Brushed and Mirror Polished wheels.  Not for Dura-Bright®.
	ALfinish	1 piece / box	GAXALF001	Polishing mop to be used on a power tool. Saves time and effort. For use with ALpolish on Brushed and Mirror Polished wheels.
	ALkit4	Kit with: 1 litre ALclean 1 ALbrush 1 tube ALpolish 1 ALfinish Manual	GAXALKIT4 (ENGLISH)	A complete kit to clean and polish your Alcoa wheels. For Brushed and Mirror Polished wheels only.  Not for Dura-Bright®.
<b>MAINTENANCE PRODUCTS</b>				
	ALLube	275 g pot	GAXALG0275	Lubricant, recommended when mounting or changing valves. <i>Introduction 2014.</i>
	ALgrease2	4 kg bucket	GAXALG4000	Mounting grease, recommended when mounting wheels to hub and replacing tyres on rim. <i>Introduction 2014.</i>
	ALprotect	500 ml bottle	GAXALPRO500EIS	Temporary winter protection to protect your aluminium wheels against salt, dirt and oxidation.  Highly recommended for Brushed and Mirror Polished wheels.

	Product	Content	Part nr.	Description
<b>PARTS</b>				
	ALcover	20 pieces / blister	GAXALCOV32	Stainless steel nut covers for 32 mm hex nuts. Suitable for Alcoa sleeved Dacromet® cap nuts (32 mm bolt hole Ø mounting) and most OE nuts (26 mm bolt hole Ø mounting).  Fits: GAX578032 and GAX578132
	ALcover	20 pieces / blister	GAXALCOV33	Stainless steel nut covers for 33 mm hex nuts. Suitable for Alcoa sleeved Dacromet® cap nuts (32 mm bolt hole Ø mounting) and most OE nuts (26 mm bolt hole Ø mounting).  Fits: GAX578232, GAX578332, GAX578432 and GAX578532
	ALgrip	1 piece	GAXALGRIP	Mounting grip to easily apply and remove nut covers.
	Discmate	1 piece	GAXDIS012000	Separator plate used to protect the wheel's mounting surface from cosmetic damage. 8 boltholes, 275 mm bolt circle diameter, 20 mm studs (M20 x 1.5).
	Discmate	1 piece	GAXDIS014000	Separator plate used to protect the wheel's mounting surface from cosmetic damage. 8 boltholes, 275 mm bolt hole circle diameter, 22 mm studs (M22 x 1.5).
	Discmate	1 piece	GAXDIS013000	Separator plate used to protect the wheel's mounting surface from cosmetic damage. 10 boltholes, 335 mm bolt circle diameter, 22 mm studs. In case of mounting with standard nuts and 26 mm bolt hole Ø.
	Discmate	1 piece	GAXDIS018000	Separator plate used to protect the wheel's mounting surface from cosmetic damage. 10 boltholes, 335 mm bolt circle diameter, 22 mm studs. In case of mounting with sleeved nuts and 32 mm bolt hole Ø.
	Inserts	16 pieces / bag	GAXINSM20	Inserts for Alcoa sleeved Dacromet® cap nuts for 19.5" wheels with 30 mm bolt holes. For use with GAX614230 and GAX614330.
	Inserts	20 pieces / bag	GAXINSM22	Inserts for Alcoa sleeved Dacromet® cap nuts for 22.5" wheels with 32 mm bolt holes. For use with GAX578032 till GAX578532.

	Product	Content	Part nr.	Description
<b>PARTS</b>				
	Sleeved Dacromet® nut M18 short	12 pieces / pack	GAX542026	Sleeved Dacromet® treated nut M18 x 1.5 for single mounting with 26 mm bolt hole Ø.
	Sleeved Dacromet® nut M18 long	12 pieces / pack	GAX542126	Sleeved Dacromet® treated nut M18 x 1.5 for dual mounting with 26 mm bolt hole Ø.
	Sleeved Dacromet® nut M20 short	16 pieces / pack incl. inserts	GAX614230	Sleeved Dacromet® treated nut M20 x 1.5 for single mounting with 30 mm bolt hole Ø.
	Sleeved Dacromet® nut M20 long	16 pieces / pack incl. inserts	GAX614330	Sleeved Dacromet® treated nut M20 x 1.5 for dual mounting with 30 mm bolt hole Ø.
	Sleeved Dacromet® nut M22 short	20 pieces / pack incl. inserts	GAX578032	Sleeved Dacromet® treated nut M22 x 1.5 for single mounting with 32 mm bolt hole Ø. (Volvo from 2005)
	Sleeved Dacromet® nut M22 long	20 pieces / pack incl. inserts	GAX578132	Sleeved Dacromet® treated nut M22 x 1.5 for dual mounting with 32 mm bolt hole Ø. (Volvo from 2005)
	Sleeved Dacromet® nut Volvo short	20 pieces / pack incl. inserts	GAX578232	Sleeved Dacromet® treated nut 7/8"-14 UNF for Volvo (till 2004). For single mounting with 32 mm bolt hole Ø.
	Sleeved Dacromet® nut Volvo long	20 pieces / pack incl. inserts	GAX578332	Sleeved Dacromet® treated nut 7/8"-14 UNF for Volvo (till 2004). For dual mounting with 32 mm bolt hole Ø.
	Sleeved Dacromet® nut Scania short	20 pieces / pack incl. inserts	GAX578432	Sleeved Dacromet® treated nut 7/8"-11 BSF for Scania. For single mounting with 32 mm bolt hole Ø.
	Sleeved Dacromet® nut Scania long	20 pieces / pack incl. inserts	GAX578532	Sleeved Dacromet® treated nut 7/8"-11 BSF for Scania. For dual mounting with 32 mm bolt hole Ø.

	Product	Content	Part nr.	Description
<b>PARTS</b>				
	Valve	1 piece	GAX40MS00N replaces GAXTR542	Short, straight nickel plated valve. For more information see Alcoa Wheel Service Manual Chapter 5.e.
	Valve	1 piece	GAX54MS00N	Medium, straight nickel plated valve. For more information see Alcoa Wheel Service Manual Chapter 5.e.
	Valve	1 piece	GAX60MS00N	Long, straight nickel plated valve. <i>Introduction 2014.</i>
	Valve	1 piece	GAX70MS07N2 replaces GAX70MS07N	Nickel plated valve with 7° angle. For more information see Alcoa Wheel Service Manual Chapter 5.e.
	Valve	1 piece	GAX70MS27N replaces GAX60MS27N	Nickel plated valve with 27° angle. For more information see Alcoa Wheel Service Manual Chapter 5.e.
	Valve	1 piece	GAX70MS45N replaces GAXTR543C	Nickel plated valve with 45° angle. For more information see Alcoa Wheel Service Manual Chapter 5.e.
	Valve	1 piece	GAX70MS60N replaces GAXTR543D	Nickel plated valve with 60° angle. For more information see Alcoa Wheel Service Manual Chapter 5.e.
	Valve	1 piece	GAX83MS00N replaces GAXTR544SP	Extra long, straight nickel plated valve. For WorkHorse® wheel only. For more information see Alcoa Wheel Service Manual Chapter 5.e.
	Extension valve	1 piece	GAX09150	150 mm POM plastic extension valve incl. dust cap. For more information see Alcoa Wheel Service Manual Chapter 5.f.

Contact:

**Alcoa Wheel Products Europe**

Industrieweg 135

3583 Paal

Belgium

T : +32 11 458 478

E : [fleet@alcoa.com](mailto:fleet@alcoa.com)

W : [www.alcoafleet.eu](http://www.alcoafleet.eu)

Distributor:



**ALCOA**